

17 Inch

Open Frame Touchmonitor

OTL173



The Flange edge version is an offshoot of GT's touchmonitor transformation that caters to another form of installation where the wall thickness of the cabinet is not too thick. The little flange at the edges of the touchmonitor allows it to fit into the opening of the cabinet with great ease. It leaves no gaps in the cabinet opening while the plane of the screen is neatly flushed with the cabinet. Those who embrace such an approach have found the Flange version a dream come true where installing the touchmonitor on to the cabinet is concerned.

As expected, this Flange version Open Framed comes with High Resolution, High Brightness, High Performance and High Reliability that could withstand 24/7 continual operation. With a 3-year warranty and sizes ranging 15-21.5 inches, it will fit nicely in retail, gaming, self-service, finance, transportation, conference, education and other industries.



Gaming



Kiosk



Vending Machine



Industrial Automation

Features & Benefits

- Open frame, with Industry quality and long lifespan
- General Touch PCAP technology, quality assurance
- Step structure, easy installation and time saving
- Range size from 15inch to 21.5 inch
- Industrial-grade raw materials, better for industry
- 3 years warranty
- Edge-to-edge after assembly, maintenance free

SPECIFICATIONS

Name	17 Inch Open Frame Touchmonitor
Model	OTL173
LCD Panel Parameters	
Display Technology	Active Matrix TFT-LCD With LED Backlight
Aspect Ratio	5:4
Active Area (W x H)	337.92mm × 270.34mm
Native Resolution	1280×1024 @ 60Hz
Response Time (Typ.)	5ms
Display Colors	16.7million
Luminance (Typ.)	250nits, with PCAP 210nits
Contrast Ratio (Typ.)	1000:1
Viewing Angle (Typ.)	Horizontal (Left/Right) CR≥10 85°/85° Vertical (Up/Down) CR≥10 80°/80°
Touch Screen Parameters	
Touch Technology	PCAP
Surface Treatment	Strengthened Optional: Anti-Glare
Active Area(W x H)	341.92mm × 274.32mm ± 0.3mm
Thickness(Total)	2.4mm ± 0.3mm
Light Transmission	≥83%
Response Time	10ms
Touch Screen Interface	USB
Touch Point	10
Overall Parameters	
Case/Bezel Color	Gray
Mounting Options	VESA: 75mm × 75mm, 100mm × 100mm, Rear Mounting, Side Mounting
Outline Dimensions (W×H×D)	384.25mm × 316.25mm × 41.0mm
Power Supply	Input Voltage Range: +12V DC ± 5%, Coaxial power jack 2.5mm pin outer diameter
On Screen Display (OSD)	Control (Back): Power, Auto, Up, Down, Menu
Power Consumption	MAX: 18W
Speaker	Optional

Operating Altitude	≤3000m
Temperature Range	Operating: 0°C to 40°C, Storage: -20°C to 60°C
Humidity (Non Condensing)	Operating: 20% to 80%, Storage: 10% to 90%
I/O	VGA, DVI, USB (Type B, For Touch)
Accessories	Cables: VGA×1, USB×1, 1.5m Length
Carton Box Dimensions	443mm (L) × 363mm (W) × 545mm (H), 4 units in one carton
Weight	Net: 3.75kg, Gross: 17.22kg
MTBF	50,000 hours demonstrated
Agency Approvals	CCC, CE, FCC
Warranty	3 years

Ordering Information

Model	Part Number	Description
OTL173-RPC03-UCD	10202010002R	17", 5:4, 250nits, P-Cap, USB, VGA & DVI, Gray

Contact sales for other options

Optional Accessories

Model	Part Number	Description
Adapter	30207010005R	12V/4.17A, DC Cable: 1500mm, DC barrel plug 2.5mm pin inner diameter
	30301010018R	UK
Power Cable	30301010011R	EU 1500mm
	30301010010R	US
DVI Cable	30302020002R	1500mm

Go to www.generaltouch.com for more products and information, or contact us.

General Touch Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Tel: 0086-28-85124120





Fax: 0086-28-85124115

E-mail: info@generaltouch.com


<http://www.generaltouch.com>

TITLE: OTL173-RC3A00-UH2A00-2.0

MARK	REVISED CONTENTS	DATE	SIGNATURE
△			



VESA:M4 THREAD
MAX:SCREW DEPTH=6mm
X8



PAY IT FORWARD
COMPANY LIMITED

ผู้จัดจำหน่าย บริษัท เพย์ อิท ฟอว์เวิร์ด จำกัด

Tel: 02-8943095


ALL DIMENSIONS ARE IN MILLIMETERS

GENERAL Touch		GeneralTouch Co.,Ltd.			
SPEC or MATERIAL REMARK	External Dimensions	384.25*316.25*41	Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>	DESIGNER:
UNIT	DATE	Active Area	DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>	wang an
mm	2022/8/22	Glass Thickness			
Projection:	Silk Print Color	Mounting	Vesa <input checked="" type="checkbox"/>	Bracket <input type="checkbox"/>	CHECKED:
		NOTES			WangZhengHua
SHEET 1 OF 2	RVE: 0.1	SCALE: 1:1	TOUCH TECHNOLOGY	P-CAP <input checked="" type="checkbox"/> SAW <input type="checkbox"/>	APPROVED:
	Tolerance: ±1.0mm			IR/PIT <input type="checkbox"/> RESISTIVE <input type="checkbox"/>	ZhouBoLin
				Non-Touch <input type="checkbox"/>	



TITLE: OTL173-RC3A00-UH2A00-2.0

MARK	REVISED CONTENTS	DATE	SIGNATURE
△			


OPTIONAL REAR MOUNT



REAR MOUNT WITH BRACKETS
HORIZONTAL OR VERTICAL



MOUNTING BRACKET
ADJUSTMENT RANGE



PAY IT FORWARD

GENERAL TOUCH LIMITED

ผู้จัดจำหน่าย บริษัท เพย์ อิท ฟอ์เวิร์ด จำกัด

Tel: 02-8943095

GeneralTouch Co.,Ltd.

SPEC or MATERIAL REMARK	External Dimensions	405.41*337.41*41	Anti-Glare	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N	DESIGNER:
UNIT	DATE	mm	DustPro	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N	wang an
Projection:	Glass Thickness	1.1MM			CHECKED:
	Silk Print Color				WangZhengHua
SHEET 2 OF 2	Mounting	Vesa <input checked="" type="checkbox"/>	Bracket	<input checked="" type="checkbox"/>	APPROVED:
RVE: 0.1	SCALE: 1:1	TOUCH TECHNOLOGY	P-CAP	<input checked="" type="checkbox"/>	ZhouBoLin
Tolerance: ±1.0mm			IR/PIT	<input type="checkbox"/>	
			Non-Touch	<input type="checkbox"/>	

ALL DIMENSIONS ARE IN MILLIMETERS